

Application

Designed for suspending stationary level adjustment lines.
Design of hanger allows for vertical adjustment.

Standard Material


Carbon Steel - Electro galvanized post manufacture

Other Options

EPDM Lined (Suffix 'RL')
Epoxy Powder Coated finish (Suffix 'PC')
Hot Dip Galvanised finish (Suffix 'HDG')
Stainless Steel construction (Suffix 'SS')

Ordering

Specify pipe size standard model and suffix.



**Compliance - US Standards MSS-SP58 (Type 1),
MSS-SP69; EG to ASTM B633 SC3, BS1706 FE/ZN12**

Model No.	Pipe Size (Inches)	Safe Working Load (lbs)	Dimension (inch)			
			Upper Steel (width)	Lower Steel (width)	Hole Size	D
EFCH022-SD	1/2"	397	0.75	0.75	0.43	0.87
EFCH028-SD	3/4"	441	0.75	0.75	0.43	1.10
EFCH035-SD	1"	485	0.75	0.75	0.43	1.38
EFCH040-SD	1-1/4"	507	0.75	0.75	0.43	1.65
EFCH048-SD	1-1/2"	529	0.75	0.75	0.43	1.89
EFCH060-SD	2"	551	0.75	0.75	0.43	2.36
EFCH075-SD	2-1/2"	595	0.98	0.98	0.55	2.87
EFCH090-SD	3"	772	0.98	0.98	0.55	3.50
EFCH105-SD	3-1/2"	816	0.98	0.98	0.55	4.13
EFCH115-SD	4"	904	0.98	0.98	0.55	4.53
EFCH140-SD	5"	948	1.18	1.18	0.55	5.51
EFCH168-SD	6"	1058	1.18	1.18	0.55	6.61
EFCH219-SD	8"	1058	1.57	1.57	0.55	8.62
EFCH273-SD	10"	1257	1.57	1.57	0.67	10.75
EFCH323-SD	12"	1610	1.57	1.57	0.67	12.72

- Due to policy of continual improvement, the specifications are subject to change without prior notice.
- Measurements are subject to 5% tolerance.
- To achieve good sound suppression do not over load fitting.